

eni i-Sint 4AM



i-Sint 4AM 5W-20, 5W-30 and 10W-30 are Synthetic Blend Passenger Car Engine Oils engineered to meet the most demanding lubrication requirements of modern gasoline fueled engines. Formulated with advanced additives and premium quality base stocks, i-Sint 4AM oils protect engines against undesirable deposits, oxidation, viscosity, and thermal breakdown. SAE 5W-20, 5W-30 and 10W-30 are Resource Conserving, meeting API service SN and ILSAC GF-5, as well as older categories: API SM, SL and previous ILSAC categories.

TYPICAL CHARACTERISTICS

SAE GRADE	METHOD		5W-20	5W-30	10W-30
Viscosity @ 40 °C	D445	cSt	48.1	60.4	66.9
Viscosity @ 100 °C	D445	cSt	8.4	10.3	10.3
Viscosity Index	D2270		151	158	141
CCS Viscosity	D5293	cP	5300 @-30°C	5600 @-30°C	5600 @-25°C
Pour Point	D97	°C	-42	-39	-36
Flash Point	D92	°C	244	244	232
Evaporative Loss, NOACK, wt%	D5800		<15	<15	<15
Specific Gravity 15°C	D4052		0.857	0.875	0.862
Zinc (ppm)	D4951		840	840	840

Performance Levels:

- API SN
- ILSAC GF-5
- Resource Conserving

PACKAGING AVAILABLE: Bulk, Totes, Drums, Pails, Cases

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.