

eni i-Sint XL 4AM



eni i-Sint XL 4AM SAE 0W-20 and 5W-30 full synthetic passenger car engine oils are designed to provide superior wear protection, improve fuel economy and extend engine life.

OTHER KEY BENEFITS AND FEATURES

- Protection against low speed pre-ignition (LSPI) in turbocharged gasoline direct injection engines (TGDI)
- Keeps engines clean by fighting sludge and varnish formation
- Superior low-temperature pumpability
- Excellent oxidation stability
- Outstanding resistance to viscosity and thermal breakdown at high temperatures
- Backward compatible with previous API “S” service categories

TYPICAL CHARACTERISTICS

SAE GRADE	Test Method	0W-20	5W-30
Specific Gravity @ 15.6 °C	D4052	0.846	0.847
Viscosity @ 40 °C, cSt	D445	44.2	61.1
Viscosity @ 100 °C, cSt	D445	8.3	10.9
Viscosity Index	D2270	166	172
Pour Point, °C	D97	-42	-39
Flash Point, COC °C	D92	226	228
CCS, cP @ °C	D5293	5600 @-35 °C	4000 @-30 °C
NOACK, wt. %	D5800	<13	<13
Zinc, wt. %	D4951	0.085	0.085
Phosphorus, wt. %	D4951	0.077	0.077
Calcium, wt. %	D4951	0.135	0.135

MEETS THE FOLLOWING PERFORMANCE REQUIREMENTS:

- API SN
- ILSAC GF-5
- Resource Conserving
- GM dexos1™ Gen 2 *Quality*

AVAILABLE PACKAGING: Bulk, Totes, Drums, Kegs, Pails, Cases

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers’ recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.