

eni Oso 4AM



eni Oso 4AM oils are high quality, anti-wear hydraulic oils designed for use in all types of hydraulic systems including rotary vane, gear type and piston hydraulic pumps.

They are formulated with a highly effective zinc/phosphorous anti-wear additive system and high quality base stocks. They possess excellent rust and oxidation inhibitors in addition to superior anti-foam characteristics.

TYPICAL CHARACTERISTICS

ISO Grade	10	22	32	46	68
Viscosity @ 40 °C cSt	10.4	22.2	32.5	44.1	65.8
Viscosity @ 100 °C cSt	2.8	4.5	5.7	7.2	9.1
Viscosity Index	116	113	118	118	113
Flash Point °C	170	218	232	246	244
Pour Point °C	-34	-39	-36	-36	-33
Specific Gravity 15.6 °C	0.852	0.849	0.852	0.855	0.863
Oxidation ASTM D943 Hrs.	4000	4000	4,000	4,000	2,500
Corrosion Copper ASTM D130	1A	1A	1A	1A	1A
Rust Protection ASTM D665 A&B	Pass	Pass	Pass	Pass	Pass
Demulsibility, minutes, max	30	30	30	30	30

Meets the following performance levels:

- Eaton/Vickers M-2950-S, I-286-S
- Vickers 35VQ25
- Denison HF-0, HF-1, HF-2
- US Steel 136
- Ford M6C32
- GM LS-2
- Cincinnati Machine

Available Packaging: Bulk, Totes, Drum, Plastic Pails, Steel Pails, Tins

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.