

eni Rotra MP LS 4AM



eni Rotra MP LS 4AM lubricants are multi-grade, multi-service, extreme pressure gear lubricants which provide excellent protection against shock loading. These products are recommended for automotive and truck rear axles and industrial applications where an API GL-5 product is specified. Rotra MP LS 4AM 80W-90 and 85W-140 lubricants incorporate the best "Clean Gear" technology available today.

In addition, eni Rotra MP LS 4AM lubricants are formulated for service fill of limited slip differentials.

TYPICAL CHARACTERISTICS

SAE VISCOSITY GRADE	80W-90	85W-140
Viscosity @ 40°C., cSt	133.9	355.2
Viscosity @ 100°C., cSt	15.1	26.7
Viscosity Index (Min.)	115	100
Brookfield Viscosity, cP	126,000 @ -26°C	80,000 @ -12°C
Pour Point, °C	-27	-12
Flash Point, COC, °C	215	220
Specific Gravity @ 15.6 °C	0.881	0.899

MEETS OR EXCEEDS THE FOLLOWING SPECIFICATIONS:

- API GL-5
- API MT-1
- SAE J2360
- Mack GO-J

AVAILABLE PACKAGING: Bulk, Totes, Drums, Kegs, Pails

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.