



STAR PREMIUM OILS

We Make Your World Run Smoother

PRODUCT DATA SHEET

STAR PREMIUM OILS XHD 10W-30 CJ-4 CODE: 640

Star Premium Oils XHD 10W-30 uses premium quality Group II base stocks and advanced additive technology, and is formulated to provide the highest levels of equipment protection available. Star Premium Oils XHD 10W-30 is recommended for heavy duty diesel engines that require API CJ-4, Cummins CES 20081, Volvo VDS-4, Mack EO-O Premium Plus, Caterpillar ECF-3. Star Premium Oils XHD 10W-30 is a premium quality, heavy-duty multi-grade oil for all-season use in diesel powered or a mix of gasoline and diesel powered equipment. It can be recommended for service requirements of all diesel and gasoline engine manufacturers. It can be recommended for both newer and older engines. Especially designed for today's high-performance, low emissions diesel engine equipped with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filter to EPA 07 compliant engines.

APPLICATIONS

Star Premium Oils XHD 10W-30 may be recommended for the following applications:

- When CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF-4 CF, CF-2 oils are required.
- When SM, SL, SJ, SH, SG, SF oils are required.
- When a US Military CID A-A-52306 performance level is required.
- When MIL-L-210E/F oils performance level is required.
- ACEA E7, E5-02, JASO DHD-1, Global DHD-1
- When GM4718M/6094M and Ford M2C153-E oils are required.
- In all diesel and gasoline engines, including turbo-charged models.
- In Caterpillar engines ECF-3
- Mack Engines EO-O, EO-N, EO-M, Premium Plus, EO-M, EO-L Plus, EO-L, EO-K/2
- In Cummins engines CES 20071, 20076, 20077, 20078, 20081
- In Volvo VDS-4, VDS-3, VDS-2, and VDS engines
- Caterpillar Engines ECF-1-a & Drive Trains TO-2
- When Allison C-3/C-4 fluids are required
- Mercedes Benz MB 228.3
- Renault, RLD-3

SELECTION

Listed below are the physical and chemical characteristics of Star Premium Oils XHD 10W-30 CJ-4 Oil. Follow equipment manufacturer recommendations and conventional guides to determine the best oil for specific applications.

SAE GRADE	10W-30
Product Code	640
Gravity, API	32
Viscosity @ 40°C, cSt	68.0
Viscosity @ 100°C, cSt	10.5
Viscosity Index	141
Pour Point: °C	-42
Sulfated Ash wt%	>1.0
Total Base Number	10
API Licensed Service:	CJ-4, CI-4 PLUS, CI-4, CH-4, CF-4, CF, CF-2, CE, CD-II/SL, SM